

新穎小型化寬頻微帶線Balun之設計

游少軍、邱正男

E-mail: 343859@mail.dyu.edu.tw

摘要

本論文提出一種新型的小型化寬頻耦合微帶線balun，使用更為小型的高通缺陷地結構來取代較大的帶距缺陷地結構。按照所提出的三個設計步驟，最後所提出的架構尺寸只有最初尺寸的8.3%。另外，這最終的balun擁有對抗支撐材料影響的免疫力，再藉由模擬與實際量測充分顯示出小巧且寬頻的結果。最後，再設計一支寬頻及多頻的單端饋入天線，整合於先前所設計的balun，使其成為平衡式饋入天線。

關鍵詞：寬頻Balun、耦合線 Balun、缺陷地結構

目錄

封面內頁 簽名頁 中文摘要	iii	ABSTRACT
iv 誌謝	v	目錄
vi 圖目錄	viii	表目錄
x 第一章 序論	1	
1.1 前言	1.1.2 研究動機與目的	
5 1.3 章節概述	5 1.4 Balun電路	
6 1.5 平衡式元件	8 第二章 新穎小型化寬頻微帶線Balun之設計	
12 2.1 簡介	12 2.2 Balun的設計過程與實驗結果 .	
13 2.3 高通與帶拒的探討	23 2.4 結論	
26 第三章 Balun之應用:平衡式天線設計與結果討論	27 3.1 平衡式寬頻天線	
之設計	31 第四章 結論	
27 3.2 平衡式多頻天線之設計	36 參考文獻	
36 參考文獻	37	

參考文獻

- [1] 東名，“行動通訊發展”，文魁資訊股份有限公司，2002.
- [2] Min Sze Yap, Lenna Ng, and Sheel Aditya, “A Triple Band Antenna for GSM and GPS Application,” IEEE vol. 2 pp. 1119-1123, December 2003.
- [3] Hyronjin Lee, Hun Nam, Yeongseog Lim, “A Design of Printed Square Loop Antenna for Omni-directional Radiation Patterns,” IEEE Radio and Wireless Conference, pp. 253-256, August 2003.
- [4] Sang-Gyu Kim, Kai Chang, “Ultrawide-band Transitions and New Microwave Components Using Double-Sided Parallel-Strip Lines,” IEEE Trans. Microwave Theory Tech., vol. 52, pp. 2148-2152, 2004.
- [5] Mongia, R., Bahl, I., and Bhartia, P. “RF and Microwave Coupled -Line Circuits,” Artech House: Norwood, MA, 1999, Ch. 11.
- [6] Steven Yu , “網路分析儀於平衡/非平衡/多埠/内箇元件的量測”，2005.
- [7] D.Ahn,J.S. Park,C.S.Kim, J . Kim, Y . Qian, and T. Itoh, “A design of the low-pass filter using the novel microstrip defected ground structure,” IEEE Trans. Microwave Theory Tech., vol. 49 , no. 1, pp. 86-93, Jan. 2001.
- [8] J .S. Park, J . S. Yun, and D. Ahn, “A design of the novel coupled- line bandpass filter using defected ground structure with wide stopband performance,” IEEE Trans.Microwave Theory Tech., 50,no.9, pp. 2037-2043, Sept. 2002.
- [9] Y. T. Lee,J. S. Lim,J. S. Park, D.Ahn, and S. Nam, “A novel phase noise reduction technique in oscillators using defected ground structure,” IEEE Microwave Wireless Compon. Lett., vol. 12, no. 2, pp. 39-41, Feb.2002.
- [10] Y. C. Jeong, S. G. Jeong, J. S. Lim, and S. Nam, “A new method to suppress harmonics using $\pi/4$ bias line combined by defected ground structure in power amplifiers,” IEEE Microwave Wireless Compon. Lett., vol. 13, no. 12, pp. 538-540, Dec. 2003.
- [11] Y. J. Sung, M.Kim, and Y . S .Kim, “Harmonics reduction with defected ground structure for a microstrip patch antenna,” IEEE antennas Wireless Propag. Lett., vol. 2, pp. 111-113,2003.
- [12] M. A. Salah-Eddin and A. M. E. Safwat, “Defected-ground coupled microstrip lines and its application in wideband baluns,” IET Microwave Antennas Propag., vol. 1, no. 4, pp. 893-899, Aug. 2007.

- [13] Hai Ta, Alexander Stameroff, Anh-Vu Pham, " Development of a Defected Ground Structure Wide Bandwidth Balun on Multilayer Organic Substrate " Microwave Conference Proceedings, Dec. 2010.
- [14] Chul-Soo Kim , Jun-Seok Park , Dal Ahn , Jae-Bong Lim, " A Novel 1-D Periodic Defected Ground Structure for Planar Circuits " Microwave and Guided Wave Letters, IEEE, Apr 2000.
- [15] Du Hai-xia, Liu Xue-guan, Guo Hui-ping, Yang Liang, " Study on Band Broadening of Planar Balun with the Defected Ground Structure " Signals Systems and Electronics (ISSSE),2010,17-20 Sept. 2010.
- [16] C. N. Chiu and H. R. Chen, " A new compact balance-fed t-monopole antenna for UMTS mobile applications, " Microw. Opt. Tech. Lett., vol. 49, pp. 1904-1907, Aug. 2007.
- [17] C. N. Chiu and H. R. Chen, " A compact and wideband balance-fed triangular-monopole antenna for DCS / PCS / UMTS / WLAN / WiMAX applications, " Microw. Opt. Tech. Lett., vol. 50, pp. 971-974, Apr. 2008.
- [18] 李建德 , " A study on the compact , UWB balun by using LTCC Technology " , Apr. 2006.