

金屬機殼上之雙頻薄型天線設計

陳家龍、邱政男

E-mail: 364790@mail.dyu.edu.tw

摘要

本篇論文主要探討將天線置於金屬機殼上之高阻抗平面(High Impedance Surface, HIS) , 使能應用於無線區域網路(Wireless Local Area Network, WLAN)。一般將天線放置於金屬機殼附近，其效能會消失，可藉由高阻抗平面來改善此缺點。本論文先設計出用於雙WLAN頻段的高阻抗平面和一個蜿蜒型天線，再以高阻抗平面放於天線的下方。過程中，使用電磁分析軟體模擬其反射損耗及天線場型，最後將模擬結果的尺寸進行實作，證實高阻抗平面及蜿蜒型天線可符合雙頻WLAN之應用。

關鍵詞：高阻抗平面、無線區域網路、蜿蜒型天線

目錄

目錄 封面內頁 簽名頁 中文摘要	iii 英文摘要
iv 誌謝	v 目錄
vi 圖目錄	viii 表目錄
x 第一章 緒論 1.1 前言	
1.1.2 研究動機與方法	2.1.3 文獻回顧
3.1.4 論文架構	3.1.2 高阻抗平面之特性
5 第二章 應用於WLAN之雙頻天線 2.1 微帶天線介紹	
6 2.2 蜿蜒型天線設計	9 2.3 金屬機殼與蜿蜒天線整合
13 第三章 高阻抗平面概述 3.1 高阻抗平面之結構	17 3.2 高阻抗平面之特性
19 第四章 高阻抗平面與蜿蜒型雙頻天線之整合設計 4.1 概述	
22 4.2 高阻抗平面三種型態比較	22 4.3 高阻抗平面與蜿蜒型天線整合
31 第五章 結論	39 參考文獻
40 圖目錄 圖2.1微帶天線示意圖	6 圖 2.2 常用輻射金屬片形狀
7 圖2.3微帶線之3D結構	8 圖2.4微帶線電磁場分布
9 圖 2.5 不均勻蜿蜒型雙頻天線幾何結構	11 圖2.6蜿蜒型雙頻天線實作圖
12 圖2.7為蜿蜒型雙頻天線模擬與量測之反射損耗圖	13 圖2.8為天線放置於金屬機殼上方示意圖
14 圖2.9為蜿蜒型雙頻天線饋入點示意圖H = 5 mm	15 圖2.10為天線、天線置於金屬機殼上方反射損耗圖
16 圖3.1二維高阻抗平面之幾何元件	18 圖3.2天線離金屬表面

參考文獻

- [1]S. Shahparnia, and O. M. Ramahi, “ Electromagnetic Interference(EMI) Reduction From Printed Circuit Boards (PCB) Using Electromagnetic Bandgap Structures,” IEEE Trans. Electromag. Compat., Vol.46, no. 4, pp.580-587, Nov. 2004.
- [2]F.-R. Yang, K.-P. Ma, Y. Qian, and T. Itoh, “ A uniplanar compact photonic-bandgap(UC-PBG) structure and its application for microwave circuit. “ IEEE Trans. Microwave Theory., Vol.47,1509-1517, 1999.
- [3]Fei-Ran Yang, Yongxi Qian, Itoh. T, “ A novel uniplanar compact PBG structure for filter and mixer applications, “ IEEE MTT-S International Microwave Symposium Digest, Vol. 3, pp.919-922, June 1999.
- [4]Zhang, M.-S.; Li, Y.-S.; Jia, C.; Li, L.-P.; “ Signal Integrity Analysis of the Traces in Electromagnetic-Bandgap structure in High-Speed Printed Circuit Boards,” IEEE Trans. Microwave Theory and Techniques, Vol.55, pp.1054-1062, May 2007.
- [5]Yeo J.; Mittra, R.; “ Bandwidth enhancement of multiband antennas using frequency selective surfaces for ground planes,” IEEE Trans. Antennas and Propagation, Vol. 4, pp.366-369, July 2004.
- [6]Ukkonen, L.;Sydanheimo, L.;Kivikoski M.; “ Patch antenna with EBG ground plane and two-layer substrate for passive RFID of metallic objects,” IEEE Trans. Antennas and Propagation Society International Symposium, Vol. 1, pp.93-96, June 2004.
- [7]F. R. Yang, K.P. Ma, Y. Qian and T.Iton, “ A Uniplanar Compact Photonic-Bandgap (UC-PBG) Structure, and Its Applications for Microwave Circuits,” IEEE Trans. Microwave Theory Tech., vol. 47, no. 8, pp. 1509-1514, Aug. 19*99.
- [8]H. H. Ohta, K. C. Lang, R. Mittra, “ Design of Two-Screen Frequency Selective Surface for C.Ku-Band Satellite Communications,” Antennas

- and Propagation Society International Symposium, Vol.21, pp. 357-360, 1983.
- [9]B. A. Munk, " Frequency Selective Surface ", Wiley, John Wiley& Sons, 2000.
- [10]D. J. Kern, D. H. Werner, A. Monorchio, L. Lanuzza and M. J.Wilhelm, " The design synthesis of multiband artificial magnetic conductors using high impedance frequency selective surfaces, " IEEE Tran. Antennas and Propagation, Vol. 153, pp.487-493, Oct. 2006.
- [11]M. A. Hiranandani, A. B. Yakovlev, A. A. Kishk, " Artificial magnetic conductors realized by frequency-selective on a grounded dielectric slab for antenna applications, " IEEE Trans. Antennas and Propagation, Vol. 153, pp.487-493, Oct. 2006.
- [12]Sanyi Zhan; Weber, R.j.; Jiming Song; " Effects of frequency Selective Surface(FSS) on Enhancing the Radiation Efficiency of Metal-surface Mounted Dipole Antennas, " IEEE / MTT-S Microwave Symposium, pp.1659-1662, June 2007.
- [13]簡嘉良, " 頻率選擇面結構於電磁用之研究 " 碩士論文,國立雲林科技大學,民國97年 [14]付云起;袁乃昌;溫熙森, " 微波光子晶體天線技術, " 北京 國防工業出版社 2006.