Preliminary Study of Using ER Fluids in Ink-jet Printhead

廖文慶、李春穎

E-mail: 8809415@mail.dyu.edu.tw

ABSTRACT

The demand for non-impact printers has grown considerably with the advent of the personal computer. At the low end, two drop-on-demand techniques predominate the market — piezoelectric impulse and thermal-bubble types. However, the high cost of piezoelectric printhead and the thermal problems encountered by thermal-bubble jet printhead restrain the use of these techniques in array-type printhead. In this study, we propose a new design of printhead with ER fluid acting as a working medium. The ink drop is controlled by the ER fluid valve. This innovative design should not only solve the aforementioned technical problems of the state-of-art printheads, but also evade the patent right problem. As a first step toward developing this new printhead, the characteristic of an ER fluid valve which controls the deflection of the elastic diaghram is investigated. Firstly, the discretized governing equation of the valve is derived. Then, the prototypes of the ER valve is designed and fabricated. The experimental measurement based on the sinusoidal response should verify the theoretical analysis. Finally, the dynamic response of the valve is studied experimentally to prove the feasibility of using this ER valve for the ink-jet printhead.

Keywords : ER Fluid ; ER Fluid valve ; Ink-jet Printhead

Table of Contents

REFERENCES

[1] H. Le, “ Ink-Jet Printing, ” IS&T ’ s Tenth International Congress on Advances in Non-Impact Printing Technologies, Tutorial Notes, 1994 .

[2] W. R. Wehl, ?Ink-Jet-Printing: The Printing State of The Art,? 1989, pp.2-46-2-52.

[3] I. Endo, Y. Yano, and H. Kobayashi, ?Electrostatic Printing Method, ? US Patent ?4106409, 1978.

[4] S. D. Howkins, and C. T. Ridgefield, ?Ink Jet Method and Apparatus, ? US Patent ?4459601, 1984.

[5] 程志堅, “ 電黏性流體的動態特性量測及智慧型結構模擬, ” 大葉大學碩士論文,中華民國八十六年六月.

[6] D. R. Gamota, and F. E. Filisko, “ Dynamic Mechanical Studies of Electrorheological Materials : Moderate Frequencies, ” Journal of Rheology, 35(3), 1991, pp. 399-425.

[7] Y. Choi, A. F. Sprecher, and H. Conrad, “ Vibration Characteristics of a Composite Beam Containing an Electrorheological Fluid, ” Journal of Intelligient Material Systems and Structures, 1, 1990, pp. 91-104.
[8] J. P. Coulter, and T. G. Duclous, “ Application of Electrorheological Materials in Vibration Control, ” Proceedings of the Second International Conference on Electrorheological Fluids, Technomic Pub. Co., Lancaster, PA, 1990, pp. 123-134.
[9] D. Brooks, “ Visco-elastic Studies on An Electro-Rheological Fluid, ” Colloids and Surfaces, 18, 1974, pp. 293-312.
[10] A. J. Simmond, “ Electro-Rheological Valve in a Hydraulic Circuit, ” IEE Proceeings-D, 138(4), 1991, pp.400-404.
[11] T. W. DeYoung, and V. B. Maltsev, “ Ink Jet Apparatus with- Improved Transducer Support, ” US Patent ?4439780, 1984.
[12] M. Whittle, R. Firoozian, D. J. Peel, and W. A. Bullough, “ Electrorheological Relaxation Times Derived from Pressure Response Experiments in the Flow Mode, ” Journal of Non-Newtonian Fluid Mechanics, 57, 1995, pp.1-25 [13] M. Whittle, R. J. Atkin, and W. A. Bullough, “ Dynamics of an Electrorheological Valve, ” International Journal of Modern Physics B, 10(23?), 1996, pp.2933-2950.
[14] C. Y. Lee, “ Finite Element Formulation of a Sandwich Beam with Embedded Electro-Rheological Fluids, ” Journal of Intelligent Material Systems and Structures, 6(5), 1995, pp.718-728.
[15] C. Y. Lee, and C. C. Chang, “ Complex Moduli of Electro-Rheological Fluid under Oscillating Shear, ” International Journal of Mechanical Science, to appear, 1999.
[16] S. P. Timoshenko, and S. Woinowsky-Krieger, ‘ Theory of Plates and Shells ’ , 2nd edition, McGraw-Hill Co, 1959.
[17] D. J. Peel, R. Stanway and W. A. Bullough, “ Dynamic Modelling of an ER Vibration Damper for Vehicle Suspension Applications, ” Smart Materials and Structures, 5, 1996, pp.591-606.