

STUDY ON THE [HOTOREACTOR DESIGN FOR THE TREATMENT OF DYE WASTEWATER BY ADVANCED OXIDATION PROCESSES

王登楷、申永順

E-mail: 9023058@mail.dyu.edu.tw

ABSTRACT

THE TREATMENT OF WASTE POLYURETHANES (PU) IS MORE AND MORE IMPORTANT, AS THE APPLICATION OF PU IS STEADILY ON THE INCREASE. THE MAJOR METHODS FOR TREATING WASTE PU INCLUDE LANDFILL, ENERGY RECOVERY, MATERIAL RECYCLING, AND CHEMICALS RECYCLING ETC. THE CHEMICALS RECYCLING IS THE CHEMICAL CONVERSION OF WASTE PU INTO THE RAW MATERIALS OF PU OR PRIMARY PETROCHEMICALS BY THE ADEQUATE CHOICE OF REAGENTS AND CATALYSTS IN THE CHEMICAL GLYCOLYSIS CONDITIONS. GLYCOLYSIS IS ONE OF THE PRINCIPAL METHODS IN CHEMICALS RECYCLING. THE FACTORS THAT AFFECT THE GLYCOLYSIS OF PU INCLUDE THE TYPES OF SOLVENT AND CATALYST, THE CONCENTRATIONS OF SOLVENT AND CATALYST AND THE REACTION TIME. IN THIS STUDY, THE GLYCOLYSIS OF PU IS INVESTIGATED TO PROVIDE THE USEFUL DATA FOR THE DESIGN OF A PILOT SCALE PLANT. THE STUDY FOR THE GLYCOLYSIS OF FLEXIBLE PU FOAM ARE CARRIED OUT AT VARIOUS FORMULAS CONSISTED OF REAGENT AND CATALYST. THE EXPERIMENTS ARE PERFORMED UNDER THE ATMOSPHERIC PRESSURE AND ISOTHERMAL CONDITION (220). DIETHYLENE GLYCOL (DEG), POTASSIUM ACETATE (CH₃COOK) ARE USED AS THE SOLVENT AND CATALYST, RESPECTIVELY. THE PROPERTIES OF GLYCOLYSIS PRODUCTS SUCH AS HYDROXYL VALUE, MASS MEAN MOLECULAR WEIGHT, VISCOSITY AND THE CONVERSION OF THE -NCOO- FUNCTIONAL GROUP IN PU ARE ANALYZED WITH DIFFERENT EXPERIMENTAL CONDITIONS. THE RESULTS INDICATE THAT THE CONCENTRATIONS WITH DEG/PU = 150%, KAC/PU = 1%, AND THE REACTION TIME = 90 MIN ARE THE BEST RATIO OF SOLVENT AND POLYURETHANE, THE CONCENTRATION OF CATALYST, AND THE REACTION TIME, RESPECTIVELY. THE AMOUNTS OF THE DISTILLATE IN THE SECOND STAGE DISTILLATION (GAS-PHASE TEMPERATURE 245 ~ 260) ARE ABOUT 13.4 ~ 43.78% UNDER THE EXPERIMENTAL CONDITIONS. SINCE THE HYDROXYL VALUE OF THE DISTILLATE OBTAINED FROM THE SECOND STAGE DISTILLATION IS CLOSED TO THAT OF THE DEG. THE RECYCLING OF PU BY THE GLYCOLYSIS WILL BE ATTRACTIVE. THE CONVERSION OF -NCOO- FUNCTIONAL GROUP IN PU AT THE OPTIMUM FORMULA (DEG/PU = 150% AND KAC/PU = 1%) CAN BE EXPRESSED BY THE TOTAL RATE EQUATION, $DX/DT = 0.014 \times (1-X) \times 3.71 \times (KAC) \times 0.6 \times (DEG) \times 1.12$. THE PROPOSED KINETIC MODEL CAN BE ACCEPTED WITH THE COEFFICIENTS OF DETERMINATION 0.8202.

Keywords : POLYURETHANE (PU) 、 GLYCOLYSIS、 PRODUCTS ANALYSIS、 KINETIC、 PURIFYING

Table of Contents

第一章 前言--P1 第二章 理論背景及文獻回顧--P4 2.1染整廢水特性簡介--P4 2.1.1染料之化學結構及發色原理--P4 2.1.2染料之分類--P5 2.1.3染料廢水之來及特性--P9 2.1.4一般染整廢水處理方法--P12 2.2光分解反應程序之理論--P16 2.2.1紫外線之特性及應用--P16 2.2.2光學基本名詞定義--P17 2.2.3光化學之反應理論--P23 2.3UV/H₂O₂光解程序之反應機制與應用--P27 2.3.1 H₂O₂之一般性質--P27 2.3.2 UV/ H₂O₂程序之反應機制--P28 2.3.3反應因子探討與應用現況--P36 2.4 Fenton 及 Photo-Fenton 處理程序之反應機制與應用--P42 2.4.1 Fenton 及 Photo-Fenton 反應機制--P42 2.4.2反應因子探討與應用現況--P48 2.5光化學反應器之設計--P58 2.5.1光源模式之基本概念--P58 2.5.2光反應器之輻射場模擬--P62 2.5.3光化學反應器之設計--P76 第三章 實驗目的--P81 第四章 實驗程序與設備--P83 4.1實驗設備與儀器--P83 4.2實驗藥品--P84 4.3實驗裝置--P86 4.4實驗步驟--P88 4.4.1背景實驗--P90 4.4.2以UV/H₂O₂ 程序處理染料水溶液--P92 4.4.3以Kenton 程序處理染料水溶液--P94 4.4.4以Photo-Fenton程序處理染料水溶液--P94 4.5分析測定方法--P95 第五章 結論與討論--P102 5.1背景實驗--P102 5.1.1染料於液相中之穩定性實驗--P102 5.1.2以H₂O₂直接分解染料水溶液實驗--P105 5.1.3以紫外線直接光解染料實驗--P105 5.2 以UV/H₂O₂ 程序處理染料水溶液之反應行為--P111 5.2.1以UV/H₂O₂ 程序處理含Yellow 86染料水溶液之反應行為--P113 5.2.2以UV/H₂O₂ 程序處理含Red 141染料水溶液之反應行為--P131 5.2.3以UV/H₂O₂ 程序處理含Blue 62染料水溶液之反應行為--P153 5.3以UV/H₂O₂ 程序處理含水溶液之光反應器設計與模式推導--P160 5.3.1光反應器之分佈模式推導--P160 5.3.2 動力式之迴歸及模擬--P166 5.3.3實驗結果與驗證--P173 5.4以Photo-Fenton/Fenton程序處理含反應性Red 141染料水溶液之

反應行為--P200 5.4.1紫外線光強度效應--P200 5.4.2溶液pH效應--P207 5.4.3染料起始濃度效應--P217 5.4.4 Fe²⁺/H₂O₂之莫耳濃度比效應--P220 5.4.5 Fe²⁺及H₂O₂進流量比率效應--P223 5.4.6光反應器尺寸效應--P225 5.4.7不同染料之反應行為比較--P227 5.5以Photo-Fenton程序處理染料Red 141溶液之光反應器設計模式推導--P231 5.5.1光反應器設計模式推導--P231 5.5.2實驗結果與驗證--P233 第六章 結論與建議--P247 6.1結論--P247 6.2建議--P250 第七章 參考資料--P251 附錄--P263

REFERENCES

TTT