

The Design of A Charge Controller for Li-ion Battery in Vehicle

林慧英、鍾翼能

E-mail: 9419737@mail.dyu.edu.tw

ABSTRACT

The electronic products are tended to light thin short and small. and Beause of environmental protection, the lithium battery times has high energy density , high output power, can charge fast , fast charging, and some useful characteristic such as light , small and low pollution. it already can became the best choice of the power supply of the products of 3C (Computer, Communication, Consumer Electronics). Therefore, there are many battery company develop such Li-ion batteries which have smaller size Li-ion battery, lighter, energy is higher energy density, have economy , security , and environmental protection. The major development in this paper is to design a low cost vehicle battery charger. This design will modify the Li-ion battery charging method. It will have shorter charging time but it will not affect the battery life. In this these, we also analyze its character and performance. Moreover we also try to raise its efficiency based on the Li-ion battery character. In order to have results. We also make a real battery charger.

Keywords : battery charge、Li-ion Battery

Table of Contents

第一章 緒論	1	1.1.1 論文之組織架構	1
2 第二章 二次電池之特性簡介	2	2.1 文獻探討	2
2.2 二次電池特性之簡介	2	2.3 二次電池種類	2
2.3.1 鉛酸電池(Lead Acid)	2	2.3.2 鎳鎘電池(Ni-Cd)	2
2.3.3 鎳氫電池(Ni-H)	2	2.3.4 鋰離子電池(Li-ion)	2
2.5.1 二次電池的未來領域	2	2.4 電池保護電路	2
2.5.2 「二次電池」的發展方向	2	2.5.1 二次電池的未來領域	2
2.7 討論	2	2.5.2 「二次電池」的發展方向	2
3.1 前言	3	2.6 鋰離子二次電池的特徵	2
3.3 隔離型	3	3.2 討論	3
3.4.1 Pulse-width modulation (PWM)	3	3.3.2 非隔離型	3
3.4.2 Pulse-frequency modulation (PFM)	3	3.4.脈波寬度調變	3
3.5 電源轉換器之導通模式	3	3.6.基本架構及動作原理	3
3.6.1 降壓式轉換器(Buck Converter)	3	3.6.2 升壓式轉換器(Boost Converter)	3
3.6.3 升降壓式轉換器(Buck-Boost Converter)	3	3.6.4 反馳式轉換器(Flyback Converter)	3
3.6.5 順向式轉換器(Forward Converter)	3	3.6.6 推挽式轉換器(Push-Pull Converter)	3
3.6.7 半橋式轉換器(Half Bridge converter)	3	3.6.8 全橋式轉換器(Full Bridge converter)	3
3.7 討論	3	3.7 討論	3
4.1 控制系統設計	4	4.1 設計	4
4.2 充電模式	4	4.2.1 鋰離子充電過程	4
4.3 連續導通模式分析	4	4.3.1 連續與不連續導通模式之邊界條件分析	4
4.4 不連續導通模式分析	4	4.4.1 連續導通模式分析	4
4.5 設計程序	5	4.4.2 不連續導通模式分析	5
4.6 protel電路佈局	5	4.5 設計程序	5
4.8 討論	5	4.6.電路佈局	5
5.1 實際電路測試	5	5.2 實測電路波形	5
5.3 結論	5	5.3 結論	5
6.1 參考文獻	6	6.2 第六章 結論與未來研究方向	6
			65

REFERENCES

- [1] N.Scholey , “ Rechargeable batteries for mobile communication, ” Electronics and Communication Engineering Journal, 1995,pp.93-96.
- [2] J.D.Shepard, L.Bush, “ Market trends in smart battery for portable electronics ” , Proceedings of The 13th Annual Battery Conference on application and Advances, 1998, PP251-253.
- [3] M.J.Riezenman, “ The search for battery batteries, IEEE Spectrum, Vol325, 1995, pp51-56.

- [4] J.McDowall, " Substation battery options-present and future ", IEEE transmission and Distribution Conference, Vol.2, 1999,pp.518-522 [5] 李立中 , "鋰離子二次電池前景可期" , 工業材料110期 , 民國八十五年二月 [6] B.Tsenter,M.Golod, " Lithium-ion battery software safety protection IEEE Aerospace and Electronics System Magazine , Vol.139, 1998, pp.23-25.
- [7] 楊家諭 , 鄭賢豪 , "二次鋰離子電池的安全性" , 工業材料117期 , pp. 71-78 , 民國八十五年九月。
- [8] D. Linden, Handbook of Batteries, McGraw-Hill,Inc., 1995.
- [9] K. Scott, Electrochemical Reaction Engineering, Academic Press, 1991.
- [10] D. Perrone and S. D. Stefano, "Survey of lithium-ion battery performance for potential use in NASA missions," Energy Conversion Engineering Conference, 1997, pp.39-41.
- [11] J. A. Carcone, " Performance of lithium-ion battery systems " , WESCON/94. Idea/Microelectronics. Conf. Rec., 1994, pp.242-248.
- [12] A. Jossen, V. Spath, H. Doring, J. Garche, " Battery management systems (BMS) for increasing battery life time, " INTELEC Conf. Rec. 3-1, 1999.
- [13] M. W. Juzkow, S. T. Mayer, " Design considerations for lithium-ion cells. Part . Cell components, " Proceedings of The 12th Annual Battery Conference on Applications and Advances, 1997, pp.181-188.
- [14] K. S. Nanjundaswamy, H. D. Friend, C. O. Kelly, D. J.Standlee, R. L. Higgins, " Electrode fabrication for Li-ion: processing, formulations and defects during coating, " Energy Conversion Engineering Conference, 1997, pp.42-45.
- [15] 「小型二次電池市場與技術專輯」 , 工業技術研究院-工業材料研究所 , 1996.
- [16] J. C. Flynn, C. Marsh, " Development and experimental results of continuous coating technology for lithium-ion electrodes, " Proceedings of The 13th Annual Battery Conference on Applications and Advances, 1998, pp. 81-84.
- [17] 薛立人 , " 二次電池之回顧與展望 " 工業材料 , 146期 p70-75(1999) [18] 張維志 , " 小型二次電池市場分析 " 小型二次電池市場與技術專輯 , 工業材料系列叢書 , 第七期 , p19-22(1996)。
- [19] 姚慶意 , " 鋰離子電池之製作技術 " 小型二次電池市場與技術專輯 , 工業材料叢書 , 第七期p49-57(1996)。
- [20] 楊家諭 " 二次鋰離子電池的應用 " 工業材料 , 117期p63-70(1997)。
- [21] 洪為民 , " 鋰離子二次電池原理、特性與應用 " 小型二次電池市場與技術專輯 , 工業材料系列叢書 , 第七期p58-63(1996)。
- [22] 費定國、高昀成 " 碳材料在鋰電池之發展和應(上) , 工業材料 , 121期 , p80-88(1997)。
- [23] 許雪萍、陳金銘、施得旭、林月微、施慶意 " 鋰離子電池材料技術 " 工業材料126期86年6月。
- [24] 陳銘鋒、蔡賓賓 , " 充電式鋰電池之簡介及其最新發展趨勢 " , 材社會第66期 , 81年6月。
- [25] 新電子科技材料 [26] T.Palanisamy and P. O.BOX, " Charging techniques for a universal lead acid battery " , in Porc.Int.Prower Sources Symp,1990,pp.72-76..
- [27] E.M. Valeriote, T.G.chang and D.M. Jochim, " Fast charging of lead-acid batteries, " in Proc.Int.Battery Conference on Applications and Advances,1994,PP.33-38.
- [28] 「小型二次電池市場與技術專輯」 , 工業技術研究院-工業材料研究所 , 1996.
- [29] 李立中 , " 鋰離子二次電池前景可期 " , 工業材料110期 , 民國八十五年二月。
- [30] " 電池快速充電技術探討 " , 資訊零件組 , 1992年6月。
- [31] A.Kaswamure and T.Yanagihara, " state of Charge Estimation of Sealed Lead-Acid Battery used for Electric Vehicles " , in IEEE Power Electronics Specialists Conf.Rec., 1998, pp583-587.
- [32] 梁適安 , " 交換式電源供給器之理論與實務設計 " , 全華圖書有限公司 , 1994。
- [33] 曾國境 , " 新型高效率電力轉換器之研製 " , 大葉大學電機工程研究所碩士論文。
- [34] 江炫樟編譯 , " 電力電子學 " , 全華科技圖書股份有限公司 , 2003。
- [35] Zhao, Q., Hu, Y., Lee, F.C., Sabate, J.A., and Li, F.: ' A high efficiency DC/DC converter as the front-end stage of high intensity discharge lamp ballasts for automobiles ' . Power Electronics and Motion Control Conf. (PIEMC 2000), Beijing, China, 2000, 2, pp. 752-756.
- [36] George C.Chryssis原著梁適安譯 , " 高頻交換式電源供應器原理與設計 " 第二版 , 全華科技圖書股份有限公司 , 84年。
- [37] Copple, E.J., and Heights, A.: " High Efficiency DC Step-up Voltage Converter ' . US Patent " . 5 929 614, July 1999.
- [38] ?uk, S., and Middlebrook, R.D.: " Coupled-inductor and other extensions of a new optimum topology switching DC-to-DC converter " , Presented at Conf. on Advances in switched-mode power conversion, Pasadena, CA, USA, 2, pp. 331-347.
- [39] Mohan Undeland Robbins原著3th edition , 江炫樟編譯 , " 電力電子學 " , 全華科技圖書股份有限公司 , 92年7月。
- [40] Chin-Chiang Hua, Meng-Yu Lin ' Study of Fast Characteristics of Battery for Electric Vehicle and Implementation of Charging Monitoring System ' , 中華民國第二十一屆電力工程研討會。
- [41] K.C. Tseng and T.J. Liang " Novel high-efficiency step-up converter " , IEE Proc.-Electr. Power Appl., Vol. 151, No 2, March 2004.
- [42] 葉名財 , " 新型太陽能充放電控制器之研製 " , 大葉大學電機工程研究所碩士論文。
- [43] 陳建廷 , " 數位化太陽能充放電控制及正弦波逆流器之研製 " , 大葉大學電機工程研究所碩士論文。
- [44] C-C Chang, G-K Horng, C-L Chen " Design and Implementation of Solar Energy Conversion System With Fully-Digitized Control