

超立方體最長環與路徑容錯嵌入之研究

蘇文彥、洪春男

E-mail: 9509835@mail.dyu.edu.tw

摘要

在這篇論文當中，我們介紹超立方體圖形在相鄰點容錯之後，有Property 2H 以及Hamiltonian laceable 的性質。依據這些定理，我們可以在超立方體圖形中建構沒有錯點錯邊的最長環狀；此環的長度為 $2n-2|F_v|+4$ ，而它的容錯最多到n 個任意點。我們也可以建構沒有錯點錯邊的最長路徑，而路徑的容錯最多到n-1 的任意點。

關鍵詞：超立方體，最長環狀，最長路徑。

目錄

| | | |
|--|--|---|
| 封面內頁 簽名頁 授權書..... | iii 中文摘要..... | iv 英文摘要..... |
| 要 要..... | v 誌謝..... | vi 目錄..... |
| 錄..... | viii Chapter 1 Introduction..... | 1 Chapter 2 |
| Preliminaries..... | 4 Chapter 3 The adjacency property 2H of hypercube..... | 6 Chapter 4 The adjacency |
| Hamiltonian laceable of hypercube..... | 15 Chapter 5 The Longest ring in faulty hypercube..... | 27 Section 5.1. Hamiltonian |
| cycle..... | 27 Section 5.2. Fault-free cycle..... | 28 Chapter 6 The Longest path in faulty |
| hypercub..... | 30 Section 6.1. between two different color vertice..... | 30 Section 6.2. between two same color |
| vertice..... | 32 Chapter 7 Conclusion..... | 36 References..... |
| | | 37 |

參考文獻

- [1] J. S. Fu, "Fault-tolerant cycle embedding in the hypercube," Parallel Computing,, vol. 29, pp.821-832, (2003).
- [2] S. Y. Hsieh, "Fault-tolerant cycle embedding in the hypercube with more both faulty vertices and faulty edges," Parallel Computing, vol. 32, pp.84-91, (2006).
- [3] C. N. Hung, Y. H. Chang, and C. M. Sun, "LONGEST PATHS AND CYCLES IN FAULT HYPERCUBES," Proceedings of the IASTED ICPDCN, pp.101-110, (2006).
- [4] C. D. Park and K. Y. Chwa, "Hamiltonian properties on the class of hypercube-like networks," Information Processing Letters,,vol. 91, pp.11-17, (2004).
- [5] Abhijit Sengupta, "On ring embedding in hypercubes with faulty nodes and links," Information Processing Letters,, vol. 68, pp.207-214, (1998).
- [6] C. H. Tsai, J.J.M. Tan, T.Liang, and L.H. Hsu, "Fault-tolerant Hamiltonian laceability of hypercubes," Information Processing Letters,, vol. 83, pp.301-306, (2002).
- [7] Y. C. Tseng, "Embedding a ring in a hypercube with both faulty links and faulty nodes," Information Processing Letters,, vol. 59, pp.217-222, (1996).
- [8] S.B. Akers, B. Krishnamurthy, "A group-theoretic model for symmetric interconnection networks," IEEE Trans. Comput., vol. 38(4), pp.555-566, (1989).
- [9] Y. H. Chang, C. N Hung, "Adjacent Vertices Fault Tolerance Hamiltonian Laceability of Hypercube Graphs," Workshop on Combinatorial Mathematics and Computation Theory, vol 22, pp.301-309, (2005).
- [10] J.C. Bermond(Ed.), "Interconnection networks," Discrete Appl. Math., pp.37+38 ,(1992).
- [11] F. Buckley, F. Harary, "Distance in Graphs," Addison-Wesley,, (1990).
- [12] M. Y. Chen, S.-J. Lee, "Distributed fault-tolerant embedding of rings in hyper- cubes," Parallel Distrib. Comput., vol. 11 p.63-71, (1991).
- [13] J.H. Chang, C.S. Shin, K.Y. Chwa, "Ring embedding in faulty star graphs," IEICE Trans. Fund., E82-A (9), pp.1953-1964, (1999).
- [14] D.F. Hsu, "Interconnection Networks and Algorithms," Networks,, vol. 23 (4), (1993).
- [15] S. Y. Hsieh, "Embedding longest fault-free paths onto star graphs with more vertex faults," Theoretical Computer Science,, vol. 337, pp.370-378, (2005).
- [16] S.Y. Hsieh, G.H. Chen, C.W. Ho, "Embed longest rings onto star graphs with vertex faults," Proceedings of the International Conference on Parallel Processing,, pp.140-147, (1998).

- [17] S.Y. Hsieh, G.H. Chen, C.W. Ho, " Fault-free Hamiltonian cycles in faulty ar- rangement graphs, " IEEE Transactions on Parallel and Distributed Systems,, vol. 10(3), pp.223-237, (1999).
- [18] S.Y. Hsieh, G.H. Chen, C.W. Ho, " Hamiltonian-laceability of star graphs, " Net- works,, vol. 36, pp.225-232, (2000).
- [19] S.Y. Hsieh, G.H. Chen, C.W. Ho, " Longest fault-free paths in star graphs with vertex faults, " Theoret. Comput. Sci., vol. 262, pp.215-227, (2001).
- [20] S.Y. Hsieh, G.H. Chen, C.W. Ho, " Longest fault-free paths in star graphs with edge faults, " IEEE Trans. Comput., vol. 50(9), pp.960-971, (2001).
- [21] C.N. Hung and K.C. Hu, " Fault-tolerant Hamiltonian laceability of bipartite hypercube-like networks, " The Proceedings of ICS, pp.1145-1149, (2004).
- [22] F.T. Leighton, " Parallel Algorithms and Architectures Arrays, Trees and Hy- percubes, " Morgan Kaufmann, San Mateo,, (1992).
- [23] S. Latifi, S.Q. Zheng, N. Bagherzadeh, " Optimal ring embedding in hypercubes with faulty links, " Proceedings of the IEEE,, pp.178-184, (1992).
- [24] J. H. Park, Hee-Chul Kim, " Longest paths and cycles in faulty star graphs, " Parallel Distrib. Comput., vol. 64, pp.1286-1296, (2004).
- [25] Abhijit Sengupta, " On ring embedding in hypercubes with faulty nodes and links, " Information Processing Letters,, vol. 68 , pp.207-214, (1998).
- [26] G. Simmons, " Almost all n-dimensional rectangular lattices are Hamilton lace- able, " Congr. Numer., vol. 21, pp.103-108, (1978).
- [27] Y. Saad and M.H. Schultz, " Topological properties of hypercubes, " IEEE Trans,Comput., vol. 37(7), pp.867-872, (1998).
- [28] Y. C. Tseng, S.H. Chang, J.P. Sheu, " Fault-tolerant ring embedding in star graphs with both link and node failures, " IEEE Trans. Parallel Distributed Sys- tems,, vol. 8(12), pp.1185-1195, (1997).
- [29] C.H. Tsai, J.J.M. Tan, T. Liang, L. H. Hsu, " Fault-tolerant Hamiltonian laceabil- ity of hypercubes, " Information Processing Letters,, vol. 83, pp.301-306, (2002)
- [30] D.J. Wang, " Embedding Hamiltonian cycles into folded hypercubes with link faults, " Journal of Parallel and Distributed Computing,, vol. 61(4), pp.545-564, (2001).
- [31] P.J. Yang, S.B. Tien, C.S. Raghavendra, " Embedding of rings and meshes onto faulty hypercubes using free dimensions, " IEEE Transactions on Computers,, vol. 43(5), p.608-613, (1994).