

Surface Treatment on S50C Carbon Steel Die Material for Zinc Die Casting

張珈盛、胡瑞峰

E-mail: 9607721@mail.dyu.edu.tw

ABSTRACT

The mold life of die-casting is a very important character in the zinc die casting process because of mass and highly repeated pressure of die casting. The intense thermal fatigue and soldering and washout of mold caused by die casting is a main factor affecting the production rate and the good yield of AG40A zinc die-casting. Mostly inquire into the thermal fatigue, soldering and washout to aluminum die-casting the research of the mold life influence on the reference, but, the study of increase of mold life of the zinc die casting is scarce. The origin studies the main purpose is inquire into the molding material S50C, give respectively three conditions : don't the surface processing, nitriding treatment, PVD coating, again through die-casting the machine to physically die-casting 1000, 3000 and 5000 number of times. Inquire into again and analyze what surface the processing has the service life of prolonging the mold material S50C. Study the result manifestation mold material S50C after handling through the PVD coating, In spite of after the thermal fatigue and soldering and washout wait for experiment analyze, all compare the surface and did not process and nitriding treatment, there is more good performance. The nitriding treatment contain good performance, but compare with PVD coating mutually, still can not compare with PVD coating. The surface did not process then in spite of at thermal fatigue and soldering and washout etc experiments analysis under, the performance that all is very bad. Therefore, the mold material S50C by PVD coating, really can definitely prolong the service life of the mold.

Keywords : Zinc alloy, die casting mold life, nitriding treatment, S50C,PVD coating, thermal fatigue, soldering, washout

Table of Contents

封面內頁 簽名頁 授權書	iii	中文摘要	iv	英文摘要	v
誌謝	vi	目錄	vii	圖目錄	x
.....	xiv	符號說明	xv	第一章 前言	1
.....	3 2.1	壓鑄	3 2.1.1	壓鑄的定義	3 2.1.2
.....	3 2.1.3	壓鑄法的優缺點	4 2.2	鋅合金	5 2.2.1
.....	5 2.2.2	鋅壓鑄件的優缺點	7 2.3	壓鑄模具	8 2.3.1
.....	8 2.3.2	模具材料必須具備性質	10 2.4	壓鑄模具表面處理	11 2.4.1
及其特性	11 2.4.2	氮化處理	12 2.4.3	電漿化學蒸鍍	13 2.4.4
.....	13 2.4.5	滲硫處理	14 2.5	磨耗	15 2.6
18 2.7	表面接觸角	19	第三章 實驗方法及步驟	29 3.1	實驗目的
實驗材料與設備	29 3.3	實驗方法	29 3.4	熱疲勞的觀察	31 3.5
抵抗的觀察	31 3.6	沖蝕抵抗的觀察	32 3.7	接觸角或濕潤性的觀察	32 3.8
組織內部微小硬度之量測	33 3.9	金相顯微組織之觀察	33	第四章 結果與討論	44 4.1
軟鋅之探討	44 4.1.1	軟鋅表面重量比之分析	44 4.1.2	軟鋅面積百分比之分析	45
4.1.3	接觸角之分析	45 4.2	沖蝕之探討	46 4.2.1	試棒的重量損失
棒的體積損失	47 4.3	模具鋼材料S50C試棒外觀探討分析	47 4.3.1	S50C未表面處理外觀之觀察	48 4.3.2
.....	47 4.3.2	S50C滲氮表面處理外觀之觀察	48 4.3.3	S50C之PVD表面處理外觀觀察	48 4.4
料S50C試棒外觀使用SEM和EDS探討分析 .	49 4.4.1	壓鑄1000次	49 4.4.2	壓鑄3000次	50
4.4.3	壓鑄5000次	50 4.5	光學顯微鏡觀察	51 4.6	SEM觀察和EDS成分分析
4.6.1	表面未處理材料	52 4.6.2	滲氮表面處理材料	52 4.6.3	PVD表面處理材料
4.7	表面微小硬度之探討分析	54 4.8	不同表面處理硬化層和鍍層厚度之探討及分析 ...	55 4.9	電腦模擬分析鋅熔液
瞬間沖擊溫度及速度	55	第五章 結論	117	參考文獻	119

REFERENCES

- [1] 林焜昆, 壓鑄技術實務, 徐氏文教基金會出版, 民國91年再版 [2] 唐漢宗, 壓鑄學, 民國74年 [3] A. Street, The Die Casting Book, Portcullis Press Ltd., pp.3-7, 349-351, (1977) [4] A. Kaye, A. Street, Die Casting Metallurgy, Butterworth and Co. Ltd., pp.1-8, 262-273, (1982) [5]

W.Young,Precision Met.39,PP,28-31(1979) [6] S.Malm,J.Tidlund,in:Proceedings of the 10th International Die Casting Congress,Paper no.IG-T79-051,(1979) [7] 張?狸?鑄造學,全華科技圖書股份有限公司,pp.395-399,民國81年 [8] T.G.Groeneveld and A.L.Ponikvar, “ Designing for Thin-Wall Zinc Die Casting ” , International Lead Zinc Research Organization,Inc., pp.25-46,(1986) [9] Metals Handbook,Nonferrous Alloys and Special - Purpose Materials, Vol.2,10th , pp.528-535,(1990) [10] 鄭嘉慶, “ 提升AG40A鋅合金鑄件健全性之研究 ” ,大葉大學機械工程研究所碩士論文,民國95年 [11] R. W. Bruner,The Metallurgy of Die Casting, Society of Die Casting. (1986) [12] 林煜昆,全國壓鑄工廠及資材廠商名錄,pp.92-93. 民國76年 [13] ASTM B240-01, “ Standard Specification for Zinc and Zinc-Aluminum (ZA) Alloys in Ingot Form for Foundry and Die Castings ” , Vol.02.04, (2001) [14] ASM Metals Handbook, Metallography, Structures and Phase Diagrams , Vol.8, pp.265, (1973) [15] H. Ogura, “ Casting Shrinkage of Thin Walled Castings ” , Journal of Dentistry, Vol.23,No 4,pp.239-244, (1995) [16] 邱松茂, 模具處理手冊, 金屬工業研究發展中心出版, 民國87年出版 [17] 邱議訓、邱士哲, 模具學, 全華科技圖書股份有限公司, pp.8-14 ~ 8-18, 民國94年再版 [18] S.Kalpakjian , Manufacturing Engineering and Technology , (2001) [19] 黃振賢, 金屬熱處理, 文京圖書有限公司, pp.209-215,民國89年 [20] 金重勳, 熱處理, 復文書局出版pp.177-212,民國88年 [21] 簡文通, 機械製造, 全華科技圖書股份有限公司, pp.10-9, 民國93年再版 [22] Y.Zhu,D.Schwam,J.F.Wallace and S.Birceanu, “ Evaluation of Soldering, Washout and Thermal Fatigue Resistance of Advanced-Metal Materials for Aluminum Die-casting Dies ” ,Materials Science and Engineering A379, pp. 420-431, (2004) [23] Z.W. Chen, M.Z. Jahedi, Mater. Des.20,pp. 303 – 309,(1999) [24] S. Gopal, A. Lakare, R. Shivpuri, Die Casting Engineering, May/June, pp. 70 – 81, (2000) [25] M. Yan, Z. Fan, J. Mater. Sci. 36,pp.285 – 295, (2001) [26] V.N. Yeremenko, V. Ya Natanzon, V.I. Dybkov, J. Mater. Sci. 16,pp.1748 – 1756,(1981) [27] D.M. Rishel, F.S. Petit, N. Birks, in: A.V. Levy (Ed.), Proceedings of Corrosion-Erosion-Wear of Materials at Elevated Temperatures, NACE/EPRI/LBL/DOE-FE, Berkeley, CA, 31 January – 2 February,(1990). [28] P.A. Coulon, Lubricant Eng. 42 (6) ,pp.357 – 362, (1986) [29] V. Joshi, K. Kulkarni, R. Shivpuri, R.S. Bhattachatya, S.J. Dikshit,D.Bhat, Surf.Coat.Technol.146/147,pp.338 – 343,(2001) [30] Y. Wang, Surf. Coat. Technol. 94/95,pp.60 – P63, (1997) [31] C. Mitter, F. Holler, F. Ustel, D. Heim, Surf. Coat. Technol. 125,pp.233 – 239,(2000) [32] A.Srivastava,V.Joshi,R.Shivpuri,R.Bhattacharya and S.Dixit, “ A Multilayer Coating Architecture to Reduce Heat Checking of Die Surfaces ” , Surface and Coatings Technology.164, pp.631-636,(2003) [33] Y.Wang, “ A Study of PVD Coatings and Die Materials for Extended Die-casting Die Life ” Surface and Coatings Technology.95, pp.60-63, (2003) [34] J.F. Wallace, D. Schwam, AFS Trans. 107,pp. 479 – 483, (1999) [35] J.F. Wallace, D. Schwam, Die Casting Engineering (USA), Vol. 44(3), May/June,pp. 50, 52, 54, 56 – 58,(2000) [36] J.F. Wallace, Y. Wang, D. Schwam, Die Casting Engineering- (USA),Vol. 41 (5), September/October, pp. 26, 28, 30, 32,(1997) [37] J.F. Wallace, Die Casting Management, Vol. 4 (2), March/April, pp. 16-18, 20-21, (1986) [38] R.M.Sharp,J.T.Gregory and Z.W.Chen, “ Intermetallic Phases Formed During Hot Dipping of Low Carbon Steel in A Zn-5%Al Melt at Temperatures Up to 575 ” , materials forum 16,pp.205-214,(1992) [39] Q.Han and S.Viswanathan, “ Analysis of the Mechanism of Die Soldering in Aluminum Die Casting ” , Metallurgical, Mater.Trans A 34,pp.139-146,(2003) [40] Z.W.Chen, “ Formation and Progression of Die Soldering During High Pressure Die Casting ” ,Materials Science and Engineering a 397,pp.356-369, (2005) [41] R.M.Sharp, Z.W.Chen and J.T.Gregory, “ Intermetallic Phases Formed During Hot Dipping of Low Carbon Steel in A Zn-5 Pct Al Melt at 450 ” , Metallurgical,Mater.Trans A 23,pp.2393-2400,(1992) [42] S. Gulizia, M.Z. Jahedi, E.D. Doyle, Surf. Coat. Technol. 140 (2001) [43] Z.M. Cen, D.T. Fraser, M.Z. Jahedi, Mater. Sci. Eng. A A260,pp.188-196, (1999) [44] M. Yan, Z. Fan, J. Mater. Sci. 35,pp.1661 – 1667, (2000) [45] 王清標, “ 界面活性劑在銅晶片表面潤濕行為之研究 ” , 中央大學化學工程與材料工程研究所碩士論文,民國95年 [46] ASM Metals Handbook,Atlas of Microstructures of Industrial Alloys ” , Vol.7, pp.33-34, (1972)